HP Latex 700 W Printer



Win high-value jobs, equipped with white ink, and sharpen your sustainability edge with HP Latex



Access white and produce the highest value jobs

- Extend your portfolio into high-margin stickers and window graphics with the whitest white.¹
- Print white without complexity—automatic recirculation and printhead cleaning reduce manual purging.
- Deliver vivid colors at high speed, get striking contrast using pure blacks, and expect sharp 4point text.
- Choose from a wide application range covering banners/textiles/poster paper, canvas, wallpaper, and vinvl.

Beat your deadlines with smart, efficient

- Fast saturated color up to 31 m²/hr outdoor, 21 m²/hr indoor.²
- Control print operations virtually anytime, anywhere with HP PrintOS tools, and grow with HP Learn trainings.
- Work fast processing reprints and multi-copy jobs with a smart front panel, and store up to 100 jobs.
- Enjoy fast and easy spindle-less loading and media access for rolls up to 121 lb (55 kg).

GO BEYOND—Lead with environmental certifications³

- Contribute to a comfortable⁴ working environment with water-based HP Latex Ink technology.
- Differentiate your business with environmental certifications³—including UL ECOLOGO^{®5} and
- Access the most sensitive spaces with odorless prints⁴ and compatibility with a wide range of alternative substrates.⁷
- Reduce your plastics consumption with cartonbased cartridge⁸ and labelless supplies; free recycling via HP Planet Partners.⁹

For more information, please visit http://www.hp.com/go/latex700series

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://lkc.hp.com/

 $Dynamic security \ enabled \ printer. \ Contains \ technology \ that \ may \ prevent \ cartridges \ with \ non-HP \ chips \ or \ circuitry \ from \ working \ now \ or \ in \ the \ future. \ More \ at: \ http://www.hp.com/learn/ds \ from \ working \ now \ or \ in \ the \ future.$

¹ Whitest white based on ISO/DIS 23498 compared to competitive alternatives using solvent and UV technologies under \$50,000 USD as of May, 2020. Test performed on black opaque self-adhesive vinyl (L*:4.16 – a:0,48-b:2.34) with 160% UF printmode using HP 832 1-liter White Latex Ink Cartridge. Visual opacity = 91%.

b:2,34) with 160% UF printmode using HP 832 1-liter White Latex Ink Cartridge. Visual opacity = 91%.

Outdoor mode (Banner) 4-pass, 100%. Indoor mode (SAV) 6-pass, 100%. Based on internal HP testing in September 2020 on Avery 3001. Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.

Based on internal competitive analysis with public information. Applicable to HP Latex technology compared to competitive large format printing alternatives using solvent and UV technologies. See individual product

[&]quot;Based on internal competitive analysis with public information. Applicable to HP Latex technology compared to competitive large format printing alternatives using solvent and UV technologies. See individual product data sheets for more information at https://hp.com/go/latex

Applicable to HP Latex links. Based on sensory evaluations conducted by Odournet, done according to VDI Guideline 3882 where 832 and 873 inks were characterized as "weak" in odor intensity and "neutral" for hedonic tone. There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

⁵ UL ECOLOGO® Certified HP 832, HP 872, HP 873, and 882 Latex links and HP 864, 865, 865, 865, 867, 869, and 870 PageWide XL links meet a range of stringent human health and environmental considerations. Verified as of the publishing date in September 2023. For more details, please refer to the UL ECOLOGO® database at https://spot.ul.com/main-app/products/catalog/ or see https://www.ul.com/EL

Applicable to select HP Latex printers. EPEAT registered where applicable/supported. See https://epeat.net for registration status by country.
HP applications experts have evaluated the catalog of media listed in the HP Media Locator based on internal criteria to identify those that provide alternative solutions with certain environmental benefits compared to the typical media within the same application type. The information in media locator is provided by the media substrate vendors. HP is not responsible for the veracity of the information from third-party companies published on the HP website. See https://www.hp.com/go/mediasolutionslocator

⁸ Applicable to HP 832. Plastic reduction based on moving from plastic ink cartridge to cardboard ink cartridges, with annual manufacturing saving of 33 tons of plastic based on average units of HP 831 and HP 831A ink cartridges from 2018 to 2020.

⁹ Program availability varies. For details, see https://hp.com/hprecycle

Technical specifications

Print				
Printing modes	105 m²/hr - Max Speed (1-pass) 31 m²/hr - High Speed (4-pass) 21 m²/hr - Production Fast (6-pass) 11 m²/hr - Production Quality, Textiles and Backlits (8-pass) 16 m²/hr - High Saturation (12-pass) 12 m²/hr - High Saturation Backlits and Textiles (14-pass) 17 m²/hr - White Spot (60%) 9 m²/hr - White Overflood (60%) 3 m²/hr - White Underflood (100%) 2 m²/hr - 3 Layers Day & Night (160%) 1			
Print resolution	Up to 1200 x 1200 dpi			
Ink types	Water-based HP Latex Inks			
Ink cartridges	9 (black, cyan, light cyan, light magenta, magenta, yellow, white, HP Latex Optimizer, HP Latex Overcoat)			
Cartridge size	1L			
Printheads	10 (2 cyan/black, 2 magenta/yellow, 2 light cyan/light magenta, 2 white, 1 HP Latex Optimizer, 1 HP Latex Overcoat)			
Long-term print-to-print repeatability	95% of colors ≤ 1.5 dE2000 ²			
Media				
Handling	Roll feed, take-up reel, wiper roller ³ , media saver, automatic horizontal cutter (for vinyl, banner and canvas ⁴ , paper-based media, and film)			
Media types	Banners, self-adhesive vinyls, films, fabrics, papers, wall coverings, canvas, synthetics, mesh, textiles ⁵			
Roll size	457 to 1625-mm rolls (580 to 1625-mm rolls with full support)			
Maximum roll weight	55 kg			
Maximum roll diameter	250 mm			
Thickness	Up to 0.5 mm			
Applications	Banners; Displays; Exhibition and event graphics; Exterior signage; Indoor posters; Interior decoration; Light boxes - film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Window graphics; Stickers			
Connectivity				
Interfaces	Gigabit Ethernet (1000Base-T)			
Dimensions (W x D	x H)			
Printer	2583 x 852 x 1402 mm			
Shipping	2800 x 1130 x 1270 mm			
Operating area	2793 x 2100 mm			
Weight				
Printer	267 kg			
Shipping	374 kg			
What's in the box	HP Latex 700 W Printer, printheads, maintenance cartridge, ink mix containers (x2), printer stand, take-up reel, media feed accessory, user maintenance kit, edge holders, quick reference guide, documentation software, power cords, air purgers, 2-in spindle adaptor			
Environmental ranges				
Operating temperature	15 to 30°C			
Operating humidity	20 to 80% RH (non-condensing)			
Acoustics				
Sound pressure	60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)			
Sound power	7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep)			
Power				
Consumption	1.5-2.5 kW (5 kW peak) (printing), 95 W (ready), <4.7 W ⁵ (sleep) (<19 W ⁷ with DFE), <0.25 W (off)			
Requirements	Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 9 A max printer power cord; 13 A max curing power cord			
Certification				
Safety	IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC)			
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC)			
Environmental	ENERGY STAR®, ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT, OSHA, CE marking compliant, Meets AgBB criteria, French VOC A+, UL GREENGUARD Gold, UL ECOLOGO			
Warranty	One-year limited hardware warranty			
	· · · · · · · · · · · · · · · · · · ·			

Ordering information

HP Latex 700 W Printer

Product YOU23A

Accessories	5	
21V10A	HP Latex 600/700/800 User Maintenance Kit	
421S3A	HP Latex Media Feed Accessory	
7F3Y3A	HP Latex 700/800 Output Platen Protector Accessory	
7HR16A	HP Latex 700/800 Textile Kit Accessory	
7HR18A	HP Latex 700/800 Ink Collector Foams Kit	
7HR19A	HP Latex 630/700/800 Media Loading Accessory	
T7U73A	HP Latex 500/700/800 Wiper Roller	

Original HP printing supplies

4UU93A	HP 836 White Latex Printhead	
4UU94A	HP 836 Optimizer Latex Printhead	
4UU96A	HP 836 Latex Maintenance Cartridge	
4UV29A	HP 832 1-liter White Latex Ink Cartridge	
4UV75A	HP 832 1-liter Black Latex Ink Cartridge	
4UV76A	HP 832 1-liter Cyan Latex Ink Cartridge	
4UV77A	HP 832 1-liter Magenta Latex Ink Cartridge	
4UV78A	HP 832 1-liter Yellow Latex Ink Cartridge	
4UV79A	HP 832 1-liter Light Cyan Latex Ink Cartridge	
4UV80A	HP 832 1-liter Light Magenta Latex Ink Cartridge	
4UV81A	HP 832 1-liter Optimizer Latex Ink Cartridge	
4UV82A	HP 832 1-liter Overcoat Latex Ink Cartridge	
4UV83A	HP 832 Ink Mix Container	
4UV95A	HP 836 Black/Cyan Latex Printhead	
4UV96A	HP 836 Magenta/Yellow Latex Printhead	
4UV97A	HP 836 Light Cyan/Light Magenta Latex Printhead	
4UV98A	HP 836 Overcoat Latex Printhead	

Original HP large format printing materials

- HP PVC-free Wallpaper (UL GREENGUARD GOLD Certified⁸, FSC® certified⁹, meets AgBB criteria¹⁰)

- HP Photo-realistic Poster Paper HP Premium Satin Canvas HP Prime Matte Air GP (REACH compliant¹¹)
- HP Premium Removable Gloss Adhesive Vinyl (REACH compliant 11)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U13DCE HP 2 year Next Business Day with Defective Media Retention
U13DHE HP 3 year Next Business Day with Defective Media Retention
U13DMPE HP 1 year Post Warranty Next Business Day with Defective Media Retention
U13DSPE HP 2 year Post Warranty Next Business Day with Defective Media Retention

1 Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects.

2 The color variation between printed jobs has been measured at 12 pass mode on vinyl media. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-E2012. Sy6 colors may experience variations above 1.5 dE2000. Backlit substrates measured in transmission mode may yield different results.

3 Wiper roller is an optional accessory.

4 Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test.

5 Textile Kit Accessory required for long runs of textile and porous textile.

6 Excluding Type 2 DFE (Digital Front End) as defined in Energy Star® Product Specification for Imaging Equipment version 3.1.

7 Total power measured in sleep mode including the Digital Front End contained on the product.

8 UL GREENGUARD Gold Certification to UL 2818 demonstrates that products are certified to UIs GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.ucu.com/go or http://www.greenguard.org

9 Trademark license code PSC-C115319.

10 With HP Latex likes, prints meet AgBB criteria for health-related evaluation of VOC emissions. See http://urwellbundessamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-

http://umweltbundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-

evaluation-of-building

11 This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.

























