

Product: EZ Floor

Category: Display & Visual - Eco Solvent, Latex and UV Ink jet

Technical specifications:

Attributes

- Textured white print receptive PET film, with an optimised pressure sensitive adhesive for floor graphic applications
- Unique sharkskin coating, ink absorbent & drying tough
- No lamination required
- R10 slip certified
- Durable surface, resists pallet truck scuffing & stiletto heels
- Also perfect for application to short-pile carpet tiles
- Easy to apply & easy to remove

Property	Typical Value	Unit	Test Method
Construction			
Total Thickness	300 +/- 6	μ	Electronic micrometer
Total Weight	365 +/- 8	gsm	Internal method
Face Material (without PSA)			
Thickness	170 +/- 4	μ	Electronic micrometer
Weight	224 +/- 5	gsm	Internal method
Adhesive			
Thickness	40 +/- 5	μ	Electronic micrometer
180° Peel Adhesion (SS)	16 +/- 1	N/25mm	FINAT 1 (Modified) 200μ Thickness / 25mm strip/ 30min dwell
Adhesive App. Temperature	+5 to +50	°C	Internal Method
Adhesive Service Temperature	-40 to +180	°C	Internal Method
Liner			
Liner Thickness	93 +/- 3	μ	Electronic micrometer
Liner Weight	99 +/- 3	gsm	Internal method

Recommended Conditions

Print room	10°C - 30°C	30% - 65% RH
Usage	-40°C - 180°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH

Conversion+

- | | |
|--|---|
| <input type="checkbox"/> Flat bed cutters | <input type="checkbox"/> Cold overlaminating |
| <input type="checkbox"/> Friction bed cutters | <input checked="" type="checkbox"/> Eco Solvent |
| <input type="checkbox"/> Die cutters | <input checked="" type="checkbox"/> Latex |
| <input type="checkbox"/> Thermal transfer screen | <input type="checkbox"/> Solvent |
| <input type="checkbox"/> Screen printing | <input checked="" type="checkbox"/> UV Ink jet |
| <input type="checkbox"/> Printing offset | |